

Transmitter 1



E1 Vetta on/off

Aerial antenna internal
Power supply Lithium battery 3,7V 1.100 mA
Charged battery autonomy at 20 °C approx. 50 hrs.
Protection level IP65
Dimensions 170x74x81 mm
Weight 400 gr
(SAMPLE IMAGE)



PRODUCT

Model: E1 Vetta on/off

ACTUATOR

Actuator 1:	3 positions (1) - 0 - (1) momentary toggle switch
Actuator 2:	3 positions (1) - 0 - (1) momentary toggle switch
Actuator 3:	3 positions (1) - 0 - (1) momentary toggle switch
Actuator 4:	3 positions (1) - 0 - (1) momentary toggle switch
Actuator 5:	START/HORN 3 positions (1) - 0 - (1) momentary toggle switch

COMPONENTS

Auto switch-off: 10 min.

Backup unit:	No
Battery:	LI-PO Internal Battery 3,7V 1.100 mA
Frequency band:	434MHz CE mark
Key switch:	Electronic Key Switch
Power adapter:	ELCA-CLIP USB + Power Adapter 100-240Vac
Radiocontrol's support belt:	Waistbelt for Vetta
Transmission mode:	Frequency Hopping

Receiver 1



AR E1 Flexi-SW (12-24Vdc)

Built-in antenna (optional: external)

Power supply 12-24 Vdc

16 NO commands (2 NO + NC)

4 digital feedback inputs

1 slot for expansion cards

STOP Cat. 3 PL d (ISO 13849-1)

Maximum contact rating: command 10 A, STOP 4 A, SAFETY 4 A, TLC 10 A

Maximum contact voltage 30 Vdc

Protection rating IP65

Dimensions 135 x 255 x 85 mm

Weight 1.6 kg

PRODUCT

Model: AR E1 Flexi-SW (12-24Vdc)

COMPONENTS

Antenna Type:	Internal
Expansion board (FLEXI):	no
Frequency band:	434MHz CE mark
Manual, Packaging:	PACK+MAN RX MAGO FLEXI
Output type:	PG21 Cable glands
Power Supply:	12-24Vdc
Receiving unit wiring connection:	Not wired
