

Table 5

code	spool type
A	
B	
C	
D	
E	
F	
G	
H	
M	
N	
O	
P	
Q	
R	
S	
* K	
** L	

Table 6

code	spool control
1	
2	
3	
4	
5	
6	
7	
8	
9	
10	
11	
* 13	
* 16	
** 13R	
** 12	

Table 7

code	incorporated microswitch
E	 microswitch type Omron-V 165 I C5

Table 8

code	operation feature
P	 on-off pneumatic control; 5-10 bar; ports G1/4
H	 on-off hydraulic control; pn = 5-20 bar; ports G1/4

Table 9

code	Ports (threads)			
	P	A ; B	T	N
M	M22x1.5	M18x1.5	M22x1.5	M22x1.5
G	G1/2	G3/8	G1/2	G1/2
S	7/8-14UNF	3/4-16UNF	7/8-14UNF	7/8-14UNF

Table 10

code	feature	code	feature	code	feature
KZ		KY		KI	
KZ1		KY1		KI1	
KZ0		KY0		KI0	
KZ01		KY01		KI01	
-	without hand control				

Table 11

code	feature	port
C	Closed center	
C1	Part for power beyond sleeve (carry over)	M22x1.5
C2	Part for power beyond sleeve (carry over)	Ø14 mm M22x1.5
-	Without part for pressure carry over	G 1/2
X	Power beyond ever to tank	

Table 12

code	Used connection ports
11	P1 ; T1
12	P1 ; T2
21	P2 ; T1
22	P2 ; T2