

PTM180-30 PRO HYDRAULIC UNIT POWERED BY A PETROL ENGINE



WWW.PIERIKTECHNIEK.NL

PTM 180-30 PRO

Hydraulic unit powered by a petrol engine for mobile applications (plug and play). This hydraulic power pack is ideal for (mobile) professional applications such as circuits of aerial platforms, mini diggers, trucks, boats, brushes, the powering of hydraulic tools, hoisting booms, log splitters, cylinders, hydraulic engines, winches and other hydraulic power applications with a compatible hydraulic capacity.

The PTM hydraulic power pack is supplied fully assembled on a recessed subframe, including:

- Petrol engine
- Gear pump
- Hoses
- 4/3 control valve
- Pressure relief valve
- Hydraulic tank
- Return filter
- Manometer
- All required accessories, connections and fittings

| PTM180-30 PRO | |
|-----------------------------------|---|
| Engine type | 1 cylinder, 4-stroke,Forced cooling, 390 prof. gasoline engine |
| Max. power | 13 HP(9,6kW)/3600rpm |
| Displacement | 389 cm ³ |
| Starting system | Recoil start and Electric-start (incl. 12V charge coil) |
| Hydraulicpump | Gear pump group 2 (30 liters a min- ute) |
| Max pressure continuous | 240 bar |
| Oil Flow setting range | 20-30 liter |
| Pressure protection setting range | 56-200 bar |
| Control valve | 4/3 control valve |
| Oil control | Yes |
| Hydraulic tank | 30 liter |
| Weight excl. oil | 59 kg |
| Sound | 80dB |
| Fitting A | 400mm x3/8" hose incl. ISO 7241-B type male BSP connection |
| Fitting B | 400mm x3/8" hose incl. ISO 7241-B type female BSP connection |
| Battery | 35 Ah 12V |
| Dimensions(LxWxH) | 820 x 600 x 500 mm |



OPTION LIST

Tubular frame (Protection at the top)

Wheel kit

H46 hydraulic oil 30 liter

Diesel engine

Electric control valve (with or without remote control)

2, 3 of 4 section control valve

WITHOUT FRAME



WITH FRAME + WHEELS

